

General Information

- This product must be installed by a qualified licensed plumber in accordance with AS/NZS 3500 and all applicable local regulations and plumbing codes.
- All pipe work must be thoroughly flushed prior to installation.
- Do not remove the ceramic cartridge from the mixer when installing.
- After installation all hoses and connections must be checked for leaks.
- It is the responsibility of the installer to ensure a waterproof seal is achieved between the product and mounting surface.

Installation

IMPORTANT: Before commencing installation, turn off the water supply. While not essential, we recommend fitting isolation valves to both the hot and cold-water supply.

1. Remove product from packaging and check for damages. If the product is damaged in any way, do not install and return to the store where the item was purchased.
2. Fasten screws (12) to secure the mixer assembly in place.
3. Attach water supply to the hot and cold water inlets as marked on the body (9).
4. When all other plumbing has been fitted, turn on the water supply and check carefully for leaks. Re-tighten fittings if necessary.
5. During wall construction ensure that the mounting threads are exposed to allow fitting of the sleeves, cover plate, and handle.
6. Once the wall has been finished, remove the protective cover (15) by removing the screw (14).
7. Push the cover sleeve (4) over the body and screw into place by hand.
8. Push the cover plate (10 and 11) over the cover sleeve (4) until it is flush with the wall.
9. Fit the handle (1) onto the cartridge (8).
10. Use the allen key (13) and screw the grub screw (2) into the back of the handle to secure. Fit the hole cap (3).